



# STEALTH

# PINNACLE

## MULTI-ZONE SERIES

**12 + 1 YEAR  
WARRANTY**

### SUB ZERO HEATING

The Pinnacle heat pump units provide Sub Zero heating & cooling powered by the 2 stage / 3 cylinder variable speed compressor. Each outdoor coil has corrosion-resistant, acrylic resin coil coating to maintain energy efficiency in the harshest climates.

- HIGH EFFICIENCY, UP TO 23 SEER / 12.5 HSPF
- IDEAL FOR HARSH CLIMATES:  $-31^{\circ}\text{F}$  -  $115^{\circ}\text{F}$
- CONNECT UP TO 5 INDOOR UNITS (ZONES) TO OUTDOOR SYSTEM
- 5 OPTIONS FOR INDOOR UNIT
- COOLING RANGE:  $0^{\circ}\text{F}$  -  $115^{\circ}\text{F}$
- HEATING RANGE:  $-31^{\circ}\text{F}$  -  $75^{\circ}\text{F}$
- SOUND LEVELS DOWN TO 58 DB(A) ON OUTDOOR UNIT





MODEL		SC-18Z-HH-M2	SC-24Z-HH-M3	SC-36Z-HH-M4	SC-42Z-HH-M5
System Type		HEAT PUMP			
Number of Zones		2	2 - 3	2 - 4	2 - 5
<b>SYSTEM PERFORMANCE (Non-Ducted Indoor Units)</b>					
Cooling Capacity (Min-Max)	Btu/h	18000 (6998 - 21001)	22000 (7500 - 30000)	36000 (8871 - 40000)	42000 (8871 - 42991)
Heating Capacity (Min-Max)	Btu/h	21000 (7000 - 26000)	26000 (7500 - 31000)	36000 (8871 - 42514)	42000 (8871 - 46062)
SEER / EER		23 / 12.5	23 / 12.5	23 / 9	23 / 9
HSPF / COP		10.5 / 3.6	10.5 / 3.6	10 / 3.2	10 / 3.4
Energy Star®		YES	YES	NO	NO
<b>SYSTEM PERFORMANCE (Ducted Indoor Units)</b>					
Cooling Capacity (Min-Max)	Btu/h	18000 (6998 - 21001)	22000 (7500 - 30000)	36000 (8871 - 40000)	42000 (8871 - 42991)
Heating Capacity (Min-Max)	Btu/h	21000 (7000 - 26000)	26000 (7500 - 31000)	36000 (8871 - 42514)	42000 (8871 - 46062)
SEER / EER		14 / 8.5	14 / 8.5	14 / 7.5	14 / 7.5
HSPF / COP		9 / 3.6	9 / 3.6	9 / 3.2	9 / 3.4
Energy Star®		NO			
<b>OUTDOOR UNIT</b>					
Cooling Temperature Range	°F	0 - 115	0 - 115	0 - 115	0 - 115
Heating Temperature Range	°F	-31 - 75	-31 - 75	31 - 75	-31 - 75
Compressor Type		2 - STAGE INVERTER			
Sound Pressure Level (Cooling / Heating)	dB(A)	58 / 58		62 / 62	62 / 62
Unit Dimension (WxHxD)	in	37 5/8 x 15 5/8 x 27 5/8	38 5/8 x 16 13/16 x 31 1/8	42 13/16 x 17 5/16 x 43 7/16	42 13/16 x 17 5/16 x 43 7/16
Package Dimension (WxHxD)	in	40 7/16 x 17 7/8 x 28 7/8	42 1/2 x 19 1/8 x 33 1/8	45 1/2 x 18 7/8 x 45 1/2	45 1/2 x 18 7/8 x 45 1/2
Weight (Net / Gross)	lbs	78 / 183	174 / 185	280 / 298	282 / 291
Refrigerant Charge - R410A	oz	77.6	95.2	158.7	176.3
Coil Type		Aluminum Fin-Copper Tube / Acrylic Resin Protection			
<b>REFRIGERANT PIPING</b>					
Port Size (Liquid - Gas)	Port A (in)	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port B (in)	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port C (in)		1/4 - 3/8	1/4 - 3/8	1/4 - 3/8
	Port D (in)			1/4 - 3/8	1/4 - 3/8
	Port E (in)				1/4 - 3/8
Pre-Charge Length	ft	66	98	131	131
Pipe Length (Min / Max)	ft	10 / 164	10 / 230	10 / 246	10 / 246
Pipe Length to furthest Indoor Unit	ft	82			
Max. Pipe Elevation	ft	26	49	49	49
<b>ELECTRICAL</b>					
Power Supply		208-230V / 1Ph / 60Hz			
Rated Current Cooling	amps	22	26	32	32
Rated Current Heating	amps	22	26	32	32
MCA	amps	20	23	36	38
MOCP	amps	35	40	60	60
Main Power Wire Size	AWG	Per Local Code			
Interconnecting Wire Size	AWG	14 / 4			
LIMITED WARRANTY		12 + 1 YEAR WARRANTY			