



STEALTH

PINNACLE

DISCOVER THE
PREMIER GEM OF
HEATING AND
COOLING



- EFFICIENT INVERTER TECHNOLOGY
- INTELLIGENT DEFROST
- SELF-DIAGNOSIS
- SIMPLE OPERATION

THE HALLMARK OF ELEGANCE & FUNCTIONALITY.

With the Stealth wall mount ductless mini-splits, you can keep any room comfortable without sacrificing aesthetics. The quiet, unobtrusive design delivers advanced performance with industry-best energy efficiency rating of as high as 38 SEER in cooling and 15 HSPF in heating.

- WiFi included
- Ultra heat down to -22°F(-31°F for 36k Model)
- Energy Star® Rated (Excluding 36K Model)
- Precise airflow control
- Multiple fan speeds
- Intelligent preheating
- Low voltage start-up
- Sleek look to blend with your decor
- I-Feel function
- Privacy lock mode
- Sleep function
- Timer function
- Advanced filter options



STEALTH PINNACLE

MODEL		SC-09ZPL-HP230 / SC-09WPL-HP230	SC-12ZPL-HP230 / SC-12WPL-HP230	SC-18ZPL-HP230 / SC-18WPL-HP230	SC-24ZPL-HP230 / SC-24WPL-HP230	SC-36ZPL-HP230 / SC-36WPL-HP230
System Type		HEAT PUMP				
SYSTEM PERFORMANCE						
Cooling Capacity (Min-Max)	Btu/h	9000 (1535 - 12966)	12000 (2900 - 15354)	18000 (4094 - 21837)	22000 (6800 - 30700)	33000 (8800 - 40900)
Heating Capacity (Min-Max)	Btu/h	9000 (2388 - 13648)	12200 (3071 - 18766)	18000 (4094 - 24566)	24000 (6800 - 32000)	34600 (16700 - 49400)
SEER / EER		38 / 16.67	30.5 / 15.3	24.5 / 13.54	21.5 / 13	23 / 10.25
HSPF / COP		15 / 4.47	14 / 3.8	12 / 3.52	12 / 3.5	10.5 / 3.17
Energy Star®		YES				NO
Cooling Temperature Range	*F	0 - 129	0 - 129	0 - 129	0 - 129	0 - 115
Heating Temperature Range	*F	-22 - 75	-22 - 75	-22 - 75	-22 - 75	-31 - 75
INDOOR UNIT		SC-09WPL-HP230	SC-12WPL-HP230	SC-18WPL-HP230	SC-24WPL-HP230	SC-36WPL-HP230
Air flow (Min-Max)	CFM	206 - 424	235 - 500	353 - 736	383 - 824	441 - 824
Sound Pressure Level (Cooling / Heating)	dB(A)	19 - 46 / 19 - 46	22 - 49 / 22 - 49	34 - 51 / 34 - 51	27 - 54 / 37 - 55	36 - 55 / 36 - 55
Dehumidification	pt/hr	1.69	2.96	3.8	4.23	7.40
Condensate Drain Size (OD)	in	5/8	5/8	5/8	5/8	5/8
Unit Dimension (WxHxD)	in	39 7/8 x 12 1/8 x 8 3/4	39 7/8 x 12 1/8 x 8 3/4	44 3/16 x 13 x 9 13/16	44 3/16 x 13 x 9 13/16	53 3/16 x 12 5/8 x 10
Package Dimension (WxHxD)	in	42 7/16 x x 14 13/16 x 11 13/16	42 7/16 x x 14 13/16 x 11 13/16	46 7/8 x x 16 x 13 3/16	46 7/8 x x 16 x 13 3/16	57 x 14 x 16 5/8
Weight (Net / Gross)	lbs	29.8 / 36.4	29.8 / 36.4	36.4 / 44.1	35.3 / 41.9	42 / 52
OUTDOOR UNIT		SC-09ZPL-HP230	SC-12ZPL-HP230	SC-18ZPL-HP230	SC-24ZPL-HP230	SC-36ZPL-HP230
Compressor Type		GREE G-10 / 2 - STAGE INVERTER				
Sound Pressure Level (Cooling / Heating)	dB(A)	57 / 57	53 / 53	59 / 59	59 / 59	63 / 63
Unit Dimension (WxHxD)	in	35 13/32 x 23 1/2 x 14 7/8	35 13/32 x 23 1/2 x 14 7/8	38 5/8 x 31 1/8 x 16 13/16	38 5/8 x 31 1/8 x 16 13/16	43 5/8 x 43 1/2 x 17 5/16
Package Dimension (WxHxD)	in	37 3/16 x 24 13/16 x 16 7/16	37 3/16 x 24 13/16 x 16 7/16	42 1/2 x 33 1/8 x 19 1/8	42 1/2 x 33 1/8 x 19 1/8	45 x 44 x 19
Weight (Net / Gross)	lbs	99.2 / 105.8	105.8 / 49.4	141.1 / 152.1	147.7 / 158.8	254 / 265
Refrigerant Charge - R410A	oz	50.4	49.4	70.6	81.1	123.5
Coil Type		Aluminum Fin-Copper Tube / Acrylic Resin Protection				
REFRIGERANT PIPING						
Line Set Size (Liquid - Gas)	in	1/4 - 1/2	1/4 - 1/2	1/4 - 5/8	1/4 - 5/8	1/4 - 5/8
Pre-Charge Length	ft	25			25	
Pipe Length (Min / Max)	ft	10 / 49	10 / 98	10 / 131	10 / 164	10 / 165
Max. Pipe Elevation	ft	33	49	66	98	100
ELECTRICAL						
Power Supply		208-230V / 1Ph / 60Hz				
Rated Current Cooling	amps	6.2	6.5	10.8	16.4	19
Rated Current Heating	amps	6.9	6.9	10.8	16.4	30
MCA	amps	9	9	22	22	32
MOCP	amps	15	15	30	35	50
Main Power Wire Size	AWG	Per Local Code				
Interconnecting Wire Size	AWG	14 / 4				
LIMITED WARRANTY		12 + 1 YEAR WARRANTY				